

Commercial/Industrial COLOR CHART

SIGNATURE® 200 Standard Colors SILICONIZED POLYESTER



HAWAIIAN BLUE★
SR.32 SRI 35



CRIMSON RED★
SR.33 SRI 34



FERN GREEN★
SR.28 SRI 29



BURNISHED SLATE★
SR.28 SRI 29



ASH GRAY★
SR.48 SRI 56



SADDLE TAN★
SR.48 SRI 56




DESERT SAND★
SR.42 SRI 48



KOKO BROWN★
SR.28 SRI 30



CHARCOAL GRAY★
SR.28 SRI 30



POLAR WHITE★
SR.58 SRI 69



RUSTIC RED★
SR.36 SRI 40



LIGHT STONE★
SR.50 SRI 58



GALLERY BLUE★
SR.28 SRI 30



SOLAR WHITE★★
SR.70 SRI 84

SIGNATURE® 300 Premium Colors KYNAR 500®, HYLAR 5000®

Additional costs apply for Signature 300 finishes.



MEDIUM BRONZE★
SR.33 SRI 36



SNOW WHITE★
SR.65 SRI 79



SLATE GRAY★
SR.37 SRI 41



ALMOND★
SR.63 SRI 76



CLASSIC GREEN★
SR.28 SRI 30



BROWNSTONE★
SR.47 SRI 54



BRITRE RED
SR.49 SRI 55



HARBOR BLUE★
SR.28 SRI 30



BONE WHITE★★
SR.70 SRI 84



- Final color selection should be made from actual color chips.
- See product selection chart for gauge and color availability.
- All products available in smooth or embossed finish.
- Trim available in all colors.
- All Signature® 300 are low gloss colors.
- Polar White is a Straight Polyester.
- A 25-year limited paint warranty available for all colors upon written request. (Outside the continental United States, please inquire.)
- Signature® is a registered trademark of NCI Group, Inc. KYNAR 500® is a registered trademark of Arkema, Inc. HYLAR 5000® is a registered trademark of Solvay Solexis.
- * This color is California Title 24 compliant. Availability in certain areas may be restricted or require a surcharge.
- ★ ENERGY STAR Qualified Color

For complete performance, specifications, product limitations and disclaimers, please consult our Paint and Galvalume Plus® warranties. Upon receipt of payment in full, these warranties are available upon request for all painted or Galvalume Plus®, prime products. Contact your local Sales Representative for actual paint samples.

Commercial/Industrial Panel Profiles

What is Solar Reflectivity (SR)?

Solar reflectivity or reflectance (SR) is the ability of a material to reflect solar energy from its surface back into the atmosphere. The SR value is a number from 0 to 1.0. A value of 0 indicates that the material absorbs all solar energy and a value of 1.0 indicates it is all reflected. Energy Star requires SR testing of both new and aged roof products. New products must have an SR value of 0.25 or higher for steep slope (above 2:12) roofing and an SR value of 0.65 or higher for low slope (2:12 or less) roofing. Aged testing takes 3 years to complete, so not all products that meet the initial requirements are qualified. For more information, please go to www.energystar.gov.






What is Solar Reflectivity Index (SRI)?

The SRI is used to determine compliance with LEED requirements and is calculated according to ASTM E 1980 using values for reflectance and emissivity. Emissivity is a material's ability to release absorbed energy. To meet LEED requirements, a roofing material must have an SRI of 29 or higher for steep slope (above 2:12) roofing and an SRI value of 78 or higher for low slope (2:12 or less) roofing. For more information, please go to www.usgbc.org.



SIGNATURE® 200 - SILICONIZED POLYESTER		
	SR #	SRI #
HAWAIIAN BLUE	.32	35
CRIMSON RED	.33	34
FERN GREEN	.28	29
BURNISHED SLATE	.28	29
ASH GRAY	.48	56
SADDLE TAN	.48	56
DESERT SAND	.42	48
KOKO BROWN	.28	30
CHARCOAL GRAY	.28	30
POLAR WHITE	.58	69
RUSTIC RED	.36	40
LIGHT STONE	.50	58
GALLERY BLUE	.28	30
SOLAR WHITE	.70	84

SIGNATURE® 300 - KYNAR 500® / HYLAR 5000®		
	SR #	SRI #
MEDIUM BRONZE	.33	36
SNOW WHITE	.65	79
SLATE GRAY	.37	41
ALMOND	.63	76
CLASSIC GREEN	.28	30
BROWNSTONE	.47	54
BRITE RED	.49	55
HARBOR BLUE	.28	30
BONE WHITE	.70	84

Profile	29 GAUGE		26 GAUGE			24 GAUGE			22 GAUGE		
	Panel	Calvalume Plus®	Sig 200 (Interior Liner Only)	Calvalume Plus®	Sig 200	Sig 300	Calvalume Plus®	Sig 200	Sig 300	Calvalume Plus®	Sig 200
 "PBR" Panel	●	■	●	■	●	■	■	■	■	■	■
 "PBU" Panel	●	■	●	■	●	■	■	■	■	■	■
 "PBC" Panel	●	■	●	■		■	■		■	■	
 "PBD" Panel	●	■	●	■		■	■		■	■	
 "PBA" Panel	●	■	●	■	●	■	■	■	■	■	■

● Available in any quantity ■ May require minimum quantity